



Powerful 370 Lumens and 400m beam with wall mountable charging base







- ATEX certificated Gas Zone 0
- Powerful beam from parabolic reflector
- Powerful beam from parabolic reflector
  Supplied with a charging cradle for wall or desk mounting
  Tough polycarbonate, ABS construction
  Durable casing, ideal for heavy industrial use
  IP64 Rated
  Lightweight 650g
  Large switch can be easily operated when wearing gloves
  Battery charging indicator
  Safety release valve to remove hydrogen gases

- Safety release valve to remove hydrogen gases



Wall mountable charging base

**CLASS I DIV 1&2 GRP ABCD** 

TEMP CODE: T4 IP64

CLASS III

	Specification
31/2	High: 370   Medium: 112   Low: 19
	400 Metres
	4-30 Hours runtime
MODE	High/Medium/Low
Li-ion	3.7V 1960mAh
	6.5 Hours charging time
****	IP64
	256x136.2x170.4mm
	Searchlight: 650g with base: 980g
CODE	SA-SIGMA-RSL
	Previously: NSSAFA-SL

Supplied with: Shoulder strap and wall charging base

## **CERTIFICATION:**











GAS: Ex ia op is IIC T4 Ga (Zone 0) MINING: Ex ia Ma IECEX SIR 17.0042X



Scan for multi language information